

Safety Data Sheet

According to 1272/2008/EC (CLP)

Printing Date: 02.09.2015

Version Number: 1.0

Revision Date: 02.09.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier:

Trade name: HA Flex LVAF

1.2 Relevant identified uses of the substance or mixture, and uses advised against:

Waterproofing.

Identified uses advised against: No further relevant information available.

1.3 Details of the supplier of the safety data sheet:

Manufacturer/supplier:

De Neef Construction Chemicals BVBA Industriepark 8, 2220 Heist-op-den-Berg, Belgium.

Tel: +32 15 24 93 60 Fax: +32 15 24 80 72

Further information obtainable from: conchem@deneef.com

1.4 Emergency telephone number:

+44 (0)1235 239 670 (Multi-lingual – 24 Hours) +44 (0)1235 239 671 (Dedicated phone line for Arabic speaking countries - 24 Hours)

EHS Department, Cikarang, Indonesia - Tel. No.: - (62-21) 893-4260

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture:

Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
Resp. Sens. 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin Sens. 1	H317	May cause an allergic skin reaction.
Carc. 2	H351	Suspected of causing cancer.
STOT SE 3	H335-H336	May cause respiratory irritation. May cause drowsiness or dizziness.
STOT RE 2	H373	May cause damage to organs through prolonged or repeated exposure.
Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.

2.2 Label elements:

Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

Hazard pictograms



Printing Date: 02.09.2015

Version Number: 1.0

Trade name: *HA Flex LVAF*

		(Contd. of page 1)			
Signal wo	rd Danger				
Methylene	etermining components of labelling: ediphenyl diisocyanate, mixture of isomers nethane-4,4'-di-isocyanate				
Hazard st	tatements				
H315	Causes skin irritation.				
H319	Causes serious eye irritation.				
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.				
H317	May cause an allergic skin reaction.				
H351	Suspected of causing cancer.				
H335-H33	H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.				
H373	May cause damage to organs through prolonged or repeated exposure.				
H412	Harmful to aquatic life with long lasting effects.				
Precautio	nary statements				
P280	Wear protective gloves/protective clothing/eye protection/face protection.				
P273	Avoid release to the environment.				
P284	[In case of inadequate ventilation] wear respiratory protection.				
P305+P35	i1+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if and easy to do. Continue rinsing.	present			
P302+P35					
P337+P31	3 If eye irritation persists: Get medical advice/attention.				
Additiona	Additional information:				

Contains isocyanates. May produce an allergic reaction.

2.3 Other hazards:

Results of PBT and vPvB assessment:

PBT: Not applicable. **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterization: Mixtures:

Description: Mixture of substances listed below with non-hazardous additions.

Dangerous components:		
CAS: 6846-50-0 EINECS: 229-934-9 Reg.nr.: 01-2119451093-47-XXXX	2,2-dimethyl-1-(methylethyl)-1,3-propanediyl bis(2- methylpropanoate) Aquatic Chronic 3, H412	30-50%
CAS: 26447-40-5 EINECS: 247-714-0 Index number: 615-005-00-9	Methylenediphenyl diisocyanate, mixture of isomers Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	10-20%
CAS: 101-68-8Diphenylmethane-4,4'-di-isocyanateEINECS: 202-966-0Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373Index number: 615-005-00-9Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H31Sens. 1, H317; STOT SE 3, H335		1,0-2,0%
Additional information: For the wording of the listed risk phrases refer to section 16.		

(Contd. on page 3)

(Contd. of page 2)

Printing Date: 02.09.2015

Version Number: 1.0

Trade name: *HA Flex LVAF*

SECTION 4: First aid measures

4.1 Description of first aid measures:

General information: Get medical advice/attention if you feel unwell.

After inhalation: No special measures required.

After skin contact: Wash with plenty of soap and water.

After eye contact: Rinse cautiously with water for several minutes.

After swallowing:

Rinse mouth.

Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed:

May cause sensitisation by skin contact.

Irritating to eyes.

4.3 Indication of any immediate medical attention and special treatment needed:

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media:

Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray.

5.2 Special hazards arising from the substance or mixture: No further relevant information available.

5.3 Advice for firefighters:

Protective equipment: Wear self-contained respiratory protective device.

Additional information: Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation.

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable receptacles.

Dispose contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Safety Data Sheet According to 1272/2008/EC (CLP)

Printing Date: 02.09.2015

Version Number: 1.0

Trade name: HA Flex LVAF

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling:

Prevent formation of aerosols.

Avoid contact with skin.

Avoid contact with eyes.

Do not eat, drink or smoke when using this product.

Store in a well-ventilated place. Keep container tightly closed.

Keep only in original container.

Use only outdoors or in a well-ventilated area.

Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities:

STORAGE

Information about storage in one common storage facility: No special measures required.

Further information about storage conditions:

Protect from frost.

Store in a dry place.

Keep cool.

7.3 Specific end use(s): No further relevant information available.

Ingredients with limit values that require monitoring at the workplace:

SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.

8.1 Control parameters:

101-68-8 Diphenylmethane-4,4'-di-isocyanate				
WEL (Great Britain) Short-term value: 0,07 mg/m ³				
	Long-term value: 0,02 mg/m ³			
	Sen; as -NC	0		
PEL (USA)	Ceiling limi	t: 0,2 mg/m ³ , 0,02 ppm		
REL (USA) Long-term value: 0,05 mg/m ³ , 0,005 ppm				
	Ceiling limit: 0,2* mg/m ³ , 0,02* ppm			
	*10-min			
TLV (USA)Long-term value: 0,051 mg/m³, 0,005 ppm		value: 0,051 mg/m ³ , 0,005 ppm		
DNELs				
101-68-8 Diphenylmethane-4,4'-di-isocyanate				
Oral DNEL short term syst.		20 mg/kg bw/d (general population)		
Dermal DNEL ac	ute local eff	17,2 mg/cm2 (general population)		
		28,7 mg/cm2 (workers)		
L	(Contd. on page 5)			

(Contd. of page 3)

Safety Data Sheet According to 1272/2008/EC (CLP)

Printing Date: 02.09.2015

Version Number: 1.0

Trade name: HA Flex LVAF

		_			(Contd. of page 4)
	ļ	DNEL sh	ort term syst.	25 mg/kg bw/d (general population)	
		1	1	50 mg/kg bw/d (workers)	
	Inhalative	DNEL long term syst.		0,025 mg/m3 (general population)	
		1	!	0,05 mg/m3 (workers)	
		DNEL sh	ort term syst.	0,05 mg/m3 (general population)	
	PNECs				
	101-68-8 Diphenylmethane-4,4'-di-isocyanate				
	PNEC STP	,	1 mg/l (-)		
	PNEC fresh	hwater	1 mg/l (-)		
	PNEC mar	ine water	0,1 mg/l (-)		

Additional information: Based on the lists valid at the date of MSDS creation.

8.2 Exposure controls:

PERSONAL PROTECTIVE EQUIPMENT

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Respiratory protection:

Control exposure to ingredients with workplace control parameters if mentioned above. If no ingredients are listed, respiratory protection is generally not required.

If exposure limits are listed and may be exceeded, use approved respiratory protective equipment and filter type appropriate for the listed ingredients. (NIOSH, CEN, etc.).

Protection of hands: Protective gloves.

Material of gloves: Rubber gloves.

Penetration time of glove material:

The exact breakthrough time has to be determined by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Safety glasses with side shield protection.



A face shield should also be worn if there is potential exposure to splash or spray.

Body protection:

Use personal protective equipment as required.

Take off contaminated clothing.

(Contd. on page 6)

GBN

(Contd. of page 5)

Printing Date: 02.09.2015

Version Number: 1.0

Revision Date: 02.09.2015

Trade name: HA Flex LVAF

SECTION 9: Physical and chemical properties		
9.1 Information on basic physical and chemical properties:		
GENERAL INFORMATION Appearance: Form: Colour: Odour: Odour: Odour threshold:	Liquid. Yellow. Sweet. Not determined.	
pH-value (~):	Not determined.	
Change in conditions:- Melting point/Melting range: Boiling point/Boiling range: Flash point:	Undetermined. Not determined. > 130 °C	
Flammability (solid, gaseous):	Not applicable.	
Decomposition temperature: Self-igniting: Danger of explosion:	Not determined. Product is not self-igniting. Product does not present an explosion hazard.	
EXPLOSION LIMITS Lower: Upper: VOC Content:	Not determined. Not determined. Not determined.	
Vapour pressure: Density at 20 °C: Relative density: Vapour density: Evaporation rate:	Not determined. ~ 1 g/cm ³ Not determined. Not determined. Not determined.	
Solubility in/Miscibility with:- Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/water): Not determined.		
VISCOSITY Dynamic: Kinematic: Molecular weight	Not determined. Not determined. Not applicable.	
9.2 Other information:	No further relevant information available.	

SECTION 10: Stability and reactivity

10.1 Reactivity: Stable under normal conditions.

10.2 Chemical stability:

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions

Reacts with water.

Reacts with oxidising agents.

10.4 Conditions to avoid: No further relevant information available.

(Contd. on page 7) GBN

Safety Data Sheet According to 1272/2008/EC (CLP)

Printing Date: 02.09.2015

Version Number: 1.0

Trade name: HA Flex LVAF

(Contd. of page 6)

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide.

SECTION 11: Toxicological information

11.1 Information on toxicological effects:

ACUTE TOXICITY

LD/LC50 values relevant for classification: 101-68-8 Diphenvlmethane-4.4'-di-isocvanate

101-68-8 Dipnenyimethane-4,4 -di-isocyan			
Oral	LD50	> 10000 mg/kg (rat)	
Dermal	LD50	> 9400 mg/kg (rabbit)	
Inhalative	LC50, 4h	0,49 mg/l (rat)	

Primary irritant effect:-

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/irritation Causes serious eye irritation.

Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Suspected of causing cancer.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity:

AQUATIC TOXICITY No further relevant information available.

12.2 Persistence and degradability: No further relevant information available.

12.3 Bioaccumulative potential: No further relevant information available.

12.4 Mobility in soil: No further relevant information available.

ADDITIONAL ECOLOGICAL INFORMATION

General notes: Not known to be hazardous to water.

12.5 Results of PBT and vPvB assessment:

PBT: Not applicable.

(Contd. of page 7)

Safety Data Sheet According to 1272/2008/EC (CLP)

Printing Date: 02.09.2015

Version Number: 1.0

Trade name: HA Flex LVAF

vPvB: Not applicable.

12.6 Other adverse effects: No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods:

Recommendation:



Must not be disposed together with household garbage. Do not allow product to reach sewage system.

UNCLEANED PACKAGING

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN-Number ADR, ADN, IMDG, IATA	Not Regulated
14.2 UN proper shipping name ADR, ADN, IMDG, IATA	Not Regulated
14.3 Transport hazard class(es)	
ADR, ADN, IMDG, IATA Class	Not Regulated
14.4 Packing group ADR, IMDG, IATA	Not Regulated
14.5 Environmental hazards: Marine pollutant:	No.
14.6 Special precautions for user:	Not Regulated
14.7 Transport in bulk according to Annex II	
of MARPOL73/78 and the IBC Code:	Not Regulated
UN "Model Regulation":	Not regulated for transport.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

See Section 2 for hazard identification.

National regulations:

Other regulations, limitations and prohibitive regulations: All components EINECS listed or exempt.

(Contd. on page 9)

GBN

Printing Date: 02.09.2015

Version Number: 1.0

Revision Date: 02.09.2015

Trade name: *HA Flex LVAF*

(Contd. of page 8)

GBN

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases:

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.
H351 Suspected of causing cancer.
H373 May cause damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

Department issuing MSDS:

EHS Department, Asia Pacific Region Grace Construction Products SCIP, Canlubang, Calamba City, Laguna Philippines 4028 Tel: ++63 (02) 884-0300, Fax: ++63 (49) 549-7778

The first date of preparation: 20.04.2015

Number of revision times and the latest revision date: 1.0 / 02.09.2015